



SYNROZ®

Piston Differential Pressure Gauge MODEL GP26



Specification

- Sensing Element : Piston
- Max Line Pressure : 600 bar / 8700 psi
- Min. DP range : 0-0.3 bar / 0-4.5 psi
- Max DP range : 0-10 bar / 0-145 psi
- Accuracy : **± 2% of FSD**
- Scale starts from : 10% of FSD
- Temperature : 0°C to +80°C
(32°F to 176°F)
- Seal : Buna-N, EPDM, Viton®, Teflon
- Port orientation : Axial, Bottom, Rear
- Port size : 1/4" NPTF / BSPF
(Other porting available as per requirement)

**NEMA 4X**

Wetted Material


- Body & End-plug : Aluminium / Brass / SS 316L
- Piston : SS 316L
- Spring : SS302 / SS 316L optional
- Magnet : Ceramic
- Seal : Buna-N, EPDM, Viton®, Teflon

Additional Features

- Customised dial with customer logo
- Bidirectional scale
- Liquid filled case
- Max pointer
- Centred zero scale
- Dual Dial
- Color band scale

Case

- Bayonet case
Small : 2.0", 2.5",
Large : 4.0", 4.5", 6.0"
- Push fit case
Small : 2.0", 2.5",
Large : 4.0", 4.5", 6.0"



Glass

- Standard glass
- Acrylic glass
- Safety glass
- Toughened

Reed Switch

- SPDT : 3W, 0.25 Amp, 124 VAC / VDC
- SPDT : 60W, 1.0 Amp, 240 VAC / VDC
- SPST : 25W, 0.5 Amp, 230 VAC / VDC
- SPST : 60W, 3.0 Amp, 240 VAC / VDC

Mounting

- Direct mounting
- Front flange mounting
- Surface mounting
- 2.0" Pipe mounting